







# **PRODUCT HIGHLIGHTS**

**Small Footprint** 

Powerful 160kV Generator

High Image Resolution with 24-Bit Color

**Enhanced Material Discrimination** 

Windows Operating System with Intel® Core™ Processor

The XIS-5335S™ is a compact but powerful X-Ray Inspection System (XIS) that provides more power than any system in its cabinet size. Capable of fitting through standard doorways, the system's small footprint allows for easy relocation and installation, while the 160kV generator provides improved detection in small objects, such as bags, backpacks, and mail parcels.

Combined with Astrophysics' best-in-class software, the XIS-5335S helps operators quickly identify threats using 6-color material discrimination and high-contrast filters that provide alternative perspectives on scanned objects. Superior image quality ensures higher throughput, making the XIS-5335S the ideal space-saving solution for sites that require powerful protection against weapons, narcotics, and contraband.

The Astrophysics XIS-5335S is designed and assembled in the United States to the highest quality standards. For nearly twenty years, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners.

## **GENERAL SPECIFICATIONS**

Tunnel Size: 53.3 cm x 35.8 cm (WxH) 21.0" x 14.1"

Dimensions:1 133.1 cm x 76.4 cm x 122.5 cm

52.4" x 30.1" x 48.2" (LxWxH) Net Weight:1 297 kg (654 lbs) Shipping Weight:1 365 kg (804 lbs)

Conveyor Speed: 23 cm/s (45 ft/min) Forward or Reverse

Conveyor Height: 72.9 cm (28.7") from Floor

Conveyor Capacity: 165 kg (364 lbs) Evenly Distributed Load

### **TECHNICAL**

Wire Resolution: 40 AWG Typical, 38 AWG Standard Steel Penetration:2 39 mm Typical, 37 mm Standard

## X-RAY GENERATOR & IMAGE PERFORMANCE

Voltage: 160kV, Operating at 150kV

Tube Current: 0.7 mA

Cooling: Sealed Di-Electric Oil Bath with Forced Air **Duty Cycle:** 100%, No Warm-Up Procedure Required

Beam Direction: Diagonally Upward

## **COMPUTER & VIDEO**

Windows® OS Platform: Memory: 4 GB RAM

Storage Capacity: 1 TB HDD, 240 GB SSD

Power Conditioner: Automatic Voltage Regulator (AVR), 600 VA Display Type: Single 19" Flat Panel Color Monitor Display Resolution: 1280 x 1024; 24 Bit/Pixel Color

# **ENVIRONMENTAL**

0°C to 40°C \ 32°F to 104°F Operating Temperature: Storage Temperature: -20°C to 60°C \ -4°F to 140°F Up To 95% Non-Condensing Humidity:

# **ELECTRICAL**

110 VAC +/- 10% 50/60Hz, 15 Amp Max System Power: 220VAC +/- 10% 50/60Hz, 10 Amp Max

## **HEALTH & SAFETY**

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40)

Typical radiation leakage is less than 0.1 mR/hr

(Leakage less than 0.5 mR/hr permitted by U.S. Federal Standards)

### STANDARD FEATURES

6 Color Imaging

Color and Black/White Imaging

Geometric Image Distortion Correction High Penetration Function Organic/Inorganic Imaging

Picture Perfect Pseudo Color

Real-Time Image Manipulation

Reverse Monochrome

Atomic Z-Number Measurement

Material Discrimination

9 Quadrant Zoom Continuous Scanning Continuous Zoom Up to 64x Vertical Zoom Panning

Auto Image Archiving Image Review Save Image (RGB)

Image Annotation JPEG Conversion Print Image Capable

Multi-Tier Accessibility Network Ready

Real-Time Self Diagnostics

Baggage Counter

### **OPTIONAL FEATURES**<sup>3</sup>

Barcode Scanning Density Alert<sup>4</sup> Local Language Safe Passage® Computer Based Training Screener Assist Software

Test Case

Threat Image Projection (TIP) Software

24" Flat Panel Monitor

Custom Paint

Dual Monitors (19" or 24")

Environmental Kit Entry/Exit Roller Tables Footmat Operator Interlock

Heavy Duty Casters Long Conveyor<sup>5</sup> Mobility Kit Radiation Meter

Remote Workstation Configuration Uninterruptible Power Supply (UPS)









ISO 9001: Certified

Weight and dimensions of the system may vary depending on customization.

<sup>2</sup>As tested on Astrophysics Inc. Test Piece.

Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information

<sup>4</sup>Not available for dual-view systems or VI7.

5Conveyor length will vary depending on system's dimensions.

Due to continued product research and development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice.

Astrophysics HQ +1.909.598.5488

**Astrophysics - DC** +1.202.350.9740

**Astrophysics - HOUSTON** +1.713.357.5132

Astrophysics - EMEA +961.9.832.500/1/2

Astrophysics - INDIA +91.11.41709990

Astrophysics - ASIA +63.2.812.0033